

More choice, better quality – The EMC edge

Our tiles are designed for comfort and safety – durable, slip resistant and soft – perfect for fitness centers, yoga studios, daycare centers, retirement homes, home gyms, and more.



"Wow that was pretty terrific service. The tiles arrived on Thursday and are already in place. Looking great."

Christophe Osborn,
Ecole Bilingue de Berkeley

Tech Data

Physical Properties

Head Impact Attenuation

Test Description	ASTM	Result	Product Thickness	Certified Height
Flame Spread	E108	Class A	1.00"	2 feet
Flammability	E648	Class II	2.50"	6 feet
Toxicity	2859	Pass	3.50"	8 feet
Slip Resistance	2075	Lead Free	3.75"	10 feet
Skid Resistance	F1677	Dry 0.63, Wet .052		
Tensile Strength	E303	Dry 96, Wet 47		
Wear Resistance	D412	117.3 psi		
UV Resistances	D3884	1.64% Loss/3000c		
	QPanel QUV	<3.0/4032 ksqm		

Product Specification

Tile Size	24" X 24" + 1/8"
Tile Thickness	1"
Tile Weight	15.75 lb



EMC
ENVIRONMENTAL MOLDING CONCEPTS

14050 Day Street
Moreno Valley, CA 92553
(888) 836-2665
www.EMCMolding.com

Better Quality, More Choice
The EMC EDGE